



AUTOZON®







Door width and weight:



PRODUCT DESCRIPTION:

- o The Swing Door Operator drive unit operates with less noise, with reliable performance and safety, providing more convenience for living and working environments.
- o The Swing Door Operator is a new upgraded transformer-less drive that offers a wider range of supply power voltages. Provides interfaces such as sensors, access control, and security sensor protection, and is equipped with interfaces for magnetic electric lock and backup battery too.
- o UPS power can be configured to meet security requirements.
- o Both can realize Interlocking function between doors.
- o If touch obstacles or personnel in operation are encountered, the door will open in the opposite direction.
- o Applicable to office buildings, storefronts, banks, factories, restaurants, hotels, shopping centres, laboratories, hospitals and other places





SWING DOOR OPERATOR AZSWD202

AUTOZON®

RECOMMENDED ACCESSORIES:



AZ MRS 68 Microwave Sensor



AZ OMS 68 01 Microwave Sensor



AZ SWD KS 430 Keyswitch



AZ SWDSS 95 Safety Sensor



AZ SLD EX 72 Transmitter & Receiver



AZ SLD TLS 73 Wired Touch less Sensor



AZ SLD WLTS 74 Wireless Touch Less Sensor



AZ SLD PB WL 70 A Wireless Push Button & Receiver




AZ FS 92 Foot Sensor

DOOR LEAF OPEN TOWARD OUTSIDE





AZ RF WIFI 31 A Wifi Module

DOOR LEAF OPEN TOWARD INSIDE









OPTIONAL INTEGRATION:



FACE RECOGNITION



FINGER PRINT



RFID



QR CODE



PASSWORD



IOT



TOUCH LESS SENSOR



SAFETY DEVICES



BATTERY BACKUP

TECHNICAL SPECIFICATIONS:	AZSWD202	
Door type	Single Door	
Carrying weight	≤1 × 100 kg	
Applicable door width	≤ 1200 mm	
Power supply voltage	220 V - 240 V AC	
Motor Power	24 V BL DC / 65 W	
Opening time	3-7 s / 90° (adjustable)	
Open time	1-30 s (adjustable)	
Protection level	IP 12 D	
Working temperature	-20 ~ +55°C	
Product size (unit)	540 x 95 x 82 mm	
Product weight (unit)	6.5 Kg	