



PRODUCT DESCRIPTION:

- o The swing gate articulated operator is applicable for operation of gates with the weight of single-leaf gate up to 400 kg and the width of each swing gate shorter than 4 m.
- o The drive mode adopts the worm and worm gear to combine the pinion transmission.
- o Integrated mechanical limit for open and close position
- o Microprocessor control unit with a wide variety of setting options, such as pedestrian leaf function, automatic closing of the gate, etc.
- o Operator can be manually unlocked in any position (e.g. in the event of a power failure)
- o Connections for safety devices, such as warning light and photocell, as well as for an external device (DC 24 V), relay contact without potential
- o Fast installation and also provided with easy electrical connection



SWING GATE OPERATOR AZSW107 01

RECOMMENDED ACCESSORIES:



AZ T21W
Transmitter



AZ T22
Transmitter



AZ PC 10
Photocell



AZ PCW L11
Wireless Photocell



AZ RFPC 417M
IP Reflector Photocell



AZ KS 15
Key Switch



AZ WLKP 17
Wireless Keypad



AZ FL 19
Flash Lamp



AZ RF WIFI 31 A
Wifi Module



AZ GSM 30
GSM Module



AZ EL32
Electronic Lock



AZ CSVC 217
Car Sun Visor Clip

GATE HARDWARE:



Hinges with
Bearing



Pivot Hinges with
Roller Bearing



Adjustable Gate Hinges
with Round plate



Bi Folding
Bearing Hinges



Rotating Bearing
Wheel



Gate Stopper
for Two Leaf Gate



Gate
Stopper

OPTIONAL INTEGRATION:



FACE
RECOGNITION



FINGER
PRINT



RFID



QR CODE



PASSWORD



IOT



GSM



SAFETY
DEVICES

TECHNICAL SPECIFICATIONS:

AZSW107 01

Power supply	220 V - 240 V AC
Motor power	260 W * 2 nos
Motor Voltage	230 V AC
Maximum weight of gate	400+ 400 Kg
Maximum leaf length	3 M + 3 M
Gate Moving Speed	9° / s ~ 11° / s
Remote control distance	≥ 30 m
Max Recording of Transmitter	25 nos
Working Duty	S2, 15 min
Working temperature	-20°C ~ +70°C
Protection Class	IP 54
Product Weight	25.7 Kg