



PRODUCT DESCRIPTION:

- o Easier to drive the gate: The motor is mounted on the far end from the hinge point
- o Special sliding groove: This enables to increase the tolerance capacity against the unevenness of road surface up to 100 mm.
- o Unlimited opening angle: As far as the opener is concerned, the opening angle can be greater than 180 degree.
- o Automatic locking: This combines both closing and locking actions.
- o Microprocessor control unit with a wide variety of setting options, such as pedestrian leaf function, automatic closing of the gate, etc.
- o Operator can be manually unlocked in any position
- o Connections for safety devices, such as warning light and photocell as well as for an external device (DC 24 V), potential-free relay contact
- o Fast installation and also provided with easy electrical connection





SWING GATE OPERATOR AZSW108R 01

AUTOZON®

RECOMMENDED ACCESSORIES:



AZ T21W Transmitter



AZ WLKP 17 Wireless Keypad



AZ T22 Transmitter



AZ WIFI 31 A Wifi Module



AZ PC 10 Photocell




AZ GSM 30 GSM Module



AZ PCW L11 Wireless Photocell



AZ FL 19 Flash Lamp



AZ RFPC 417M IP Reflector Photocell



AZ SLSP 319 Solar Kit



AZ KS 15 Key Switch



AZ CSVC 217 Car Sun Visor Clip

GATE HARDWARE:



Hinges with Bearing



Pivot Hinges with Roller Bearing



Adjustable Gate Hinges with Round plate



Bi Folding Bearing Hinges



Rotating Bearing Wheel



Gate Stopper for Two Leaf Gate



Gate Stopper

OPTIONAL INTEGRATION:



FACE RECOGNITION



FINGER PRINT



RFID



QR CODE



PASSWORD



IOT



GSM



SAFETY DEVICES



BATTERY BACKUP

TECHNICAL SPECIFICATIONS:	AZSW108R 01	
Power supply	220 V - 240 V AC	
Motor power	100 W * 2 nos	
Motor Voltage	24 V DC	
Maximum weight of gate	600+ 600 Kg	
Motor Force	1000 N	
RPM	2800	
Gate Moving Speed	10°/s~15°/s	
Remote control distance	≥ 30 m	
Max Recording of Transmitter	25 nos	
Working Duty	S1	
Working temperature	-20°C ~ +70°C	
Protection Class	IP 54	
Product Weight	17 Kg	